



Utförande: Oljad ekfanér alt. svartbetsad ek och matt opalglas. Kan även tillverkas i andra träslag och ytbehandlingar på begäran. Finns för ett flertal olika ljuskällor. 26-32W kompaktlysrör alt. LED.

Montage: I tak.

Anslutning: Takkontakt vid HFF 5-ledad kabel.

Design: Fredrik Mattson 2010.

W	FÄRG/FINISH	ART
26-32W/Gx24q	Oljad ek/Oiled oak	8020-1-32
26-32W/Gx24q	Svart ek/Black oak	8020-1-36
32W/Gx24q	Oljad ek/Oiled oak	8020-1-32HFF
32W/Gx24q	Svart ek/Black oak	8020-1-36HFF
LED*	Oljad ek/Oiled oak	8022-1-32
LED*	Svart ek/Black oak	8022-1-36

HFF = Dimmbar med DALI, DSI, SwitchDim

HFF = Dimmable with DALI, DSI, SwitchDim

LED* se www.zero.se för teknisk information gällande Led.



LED* visit www.zero.se for technical information regarding LEDs.

Finish: Oiled or black stained oak veneer and matt opal glass. Available in other wood finishes and stains on request. Available with several light sources. 26-32W compact fluorescent or LED Philips Fortimo 2000 lumen.

Installation: Ceiling.

Connection: Terminal block 3x2,25mm² when HFF cable without plug.

Design: Fredrik Mattson 2010.



TAK/CEILING 12-14

VÄGG/WALL 116-117

BORD/TABLE 148