



**Utförande:** Stomme i vitlackerad aluminium. Kupa av matt opalglas. Skärm av sträckmetall, vit, svart eller koppar.

**Montage:** Dikt tak alt. vägg.

**Anslutning:** Snabbkopplingsplint 5x4mm<sup>2</sup>.

**Design:** Joel Karlsson, Krook & Tjäder Design 2011.

W	FÄRG/FINISH	ART.
26-42W/Gx24q	Vit/White	8080-1-01
42W/Gx24q	Vit/White	8080-1-01HFF
26-42W/Gx24q	Svart/Black	8080-1-06
42W/Gx24q	Svart/Black	8080-1-06HFF
26-42W/Gx24q	Koppar/Copper	8080-1-78
42W/Gx24q	Koppar/Copper	8080-1-78HFF
LED*	Vit/White	8081-1-01
LED*	Vit/White	8081-1-01HFF
LED*	Svart/Black	8081-1-06
LED*	Svart/Black	8081-1-06HFF
LED*	Koppar/Copper	8081-1-78
LED*	Koppar/Copper	8081-1-78HFF

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

LED\* se [www.zero.se](http://www.zero.se) for teknisk information gällande Led

LED\* visit [www.zero.se](http://www.zero.se) for technical information regarding LEDs.

#### TILLBEHÖR/ACCESSORY

Distans för utanpåliggande ledning 98080-1-01

Distance for external mains

Närvarosensor/Motion detector 98900-1-01

Nödljus till LED modell/Emergency light for LED model 98901-1-01

**Finish:** Base in white painted aluminium. Matt opal glass and shade in expanded metal, white, black or copper.

**Installation:** Ceiling or wall.

**Connection:** Terminal block 5x4mm<sup>2</sup>.

**Design:** Joel Karlsson, Krook & Tjäder Design 2011.

