

Utförande: Pollare i grålackerad zinkad metall alt. rostfritt stål för placering i kustnära områden. Finns i två modeller, ljus mot ett håll (asymmetrisk) samt ljus runt om (symmetrisk). Ljusaccenten på toppen som ger markeringsljus levereras standard i matt akryl, kan levereras i ett flertal färger på begäran. Finns även med uppljus genom ljusaccenten.

Montage: Passar standard fundament E7778666, D 108 mm.

Anslutning: Kopplingsplint 5x10mm².

Design: Gerhard Rehm.

W	LJUS/LIGHT	ART NR
GRÅLACKERAD ZINK/GREY PAINTED ZINCED		
35W/CDM-T/G12	Asymmetriskt/Asymmetrical	3242-1-10
35W/CDM-T/G12	Symmetriskt/Symmetrical	3241-1-10
35W/CDM-T/G12	Asym med uppljus/Asym with uplight	3243-1-10
35W/CDM-T/G12	Sym med uppljus/Symmetrical with uplight	3244-1-10
LED/2000Lm/830	Asymmetriskt/Asymmetrical	3246-1-10
LED/2000Lm/830	Symmetriskt/Symmetrical	3247-1-10
ROSTFRITT/STAINLESS STEEL		
35W/CDM-T/G12	Asymmetriskt/Asymmetrical	3242-1-91
35W/CDM-T/G12	Symmetriskt/Symmetrical	3241-1-91
LED/2000Lm/830	Asymmetriskt/Asymmetrical	3246-1-91
LED/2000Lm/830	Symmetriskt/Symmetrical	3247-1-91

Finish: Zincad and grey painted steel or in stainless steel for installation close to coast line. Available in two models, light in one direction (asymmetrical) and all around (symmetrical).. Light accent on top standard in matt acrylic. Available in different colours on request.

Installation: Fits standard foundation D 108 mm.

Connection: Terminal block 5x10mm².

Design: Gerhard Rehm.

