



Utförande: Kromad pendel och takkopp. Kupa av opalglas. D250-300 mm har stängd kupa D350-450 mm är öppen nedåt.

Montage: I takkrok, dikt tak.

Anslutning: Kopplingsplint 3x4mm². Överkopplingsbar.

W	D/MM	GLAS/GLASS	V/KG	ART
E27/max 70W	250	Opal	2,3	5270-2-20
E27/max 70W	300	Opal	2,5	5270-3-20
E27/max 70W	350	Opal	2,7	5270-4-20
E27/max 70W	400	Opal	2,9	5270-5-20
E27/max 70W	450	Opal	3,2	5270-6-20
1x26-32W/Gx24q-3	350	Opal	2,9	5373-4-20
2x26-32W/Gx24q-3	350	Opal	2,9	5374-4-20
2x32W/Gx24q-3	350	Opal	2,9	5374-4-20HFF
1x26-32W/Gx24q-3	400	Opal	2,9	5373-5-20
2x26-32W/Gx24q-3	400	Opal	2,9	5374-5-20
2x32W/Gx24q-3	400	Opal	2,9	5374-5-20HFF
1x26-32W/Gx24q-3	450	Opal	2,9	5373-6-20
2x26-32W/Gx24q-3	450	Opal	2,9	5374-6-20
2x32W/Gx24q-3	450	Opal	2,9	5374-6-20HFF
3x26-32W/Gx24q-3	450	Opal	2,9	5375-7-20
3x32W/Gx24q-3	450	Opal	2,9	5375-7-20HFF

HFF = Dimmbart driftdon. Fördunklas via SwitchDIM alt. DSI. Dali på begäran.

HFF = Dimmable ballast. SwitchDIM or DSI. Dali on request.

Finish: Chromed pendant. Shade in opal glass.

D250-300 mm are closed D350-450 mm are open.

Installation: Ceiling-hook.

Connection: Terminal block 3x4mm².

