



Utförande: Reflexlyt och lackerad metall. Bländskydd av matt akryl.

Skärmens form varierar något och kan „fluffas till“ vid behov.

Montage: I tak, pendlas i vajer.

Anslutning: Kabel och takkontakt, vid HFF kopplingsplint 5x4mm².

Design: Färg & Blanche 2012.

W	D/MM	ART
40W/2G13	550	8220-1-92
40W/2G13	550	8220-1-92HFF
55W/2G13	550	8221-1-92
55W/2G13	550	8221-1-92HFF
E27/Max 53W	550	8222-1-92
LED*	550	8223-1-92
LED*	550	8223-1-92HFF
40W/2G13	750	8220-3-92
40W/2G13	750	8220-3-92HFF
55W/2G13	750	8221-3-92
55W/2G13	750	8221-3-92HFF
LED*	750	8223-3-92
LED*	750	8223-3-92HFF

HFF = Dimmbar med DALI, DSI, SwitchDim

HFF = Dimmable with DALI, DSI, SwitchDim

LED* se www.zero.se for teknisk information gällande Led.

LED* visit www.zero.se for technical information regarding LEDs.

Finish: Reflex fabric and painted metal. Diffuser of matt acrylic. The shades are unique and can be adjusted by hand.

Installation: Ceiling, wire pendant.

Connection: Terminal block 3x4mm², when HFF terminal block 5x4mm².

Design: Färg & Blanche 2012.

