

**Utförande:** Vit- eller svartlackerad metall. Bländskydd av matt akryl.

Skärmens vinkel justeras med vajer.

**Montage:** I takkrok.

**Anslutning:** Takkontakt vid HFF kopplingsplint 5x4mm<sup>2</sup>.

**Design:** Tham & Videgård 2009.

W	MM	ART
22W/2Gx13	650	7850-1-XX
22W/2Gx13	650	7850-1-XXHFF
40W/2Gx13 + 26-42W/Gx24q	1000	7850-3-XX
40W/2Gx13 + 42W/Gx24q	1000	7850-3-XXHFF
E27/max 42W	650	7852-1-XX
E27/max 42W	1000	7852-3-XX
LED*	650	7857-1-XX
LED*	650	7857-1-XXHFF
LED*	1000	7857-3-XX
LED*	1000	7857-3-XXHFF

Färg/Color (XX) -01 vit/white, -06 svart/black

HFF = Dimmbar med DALI, DSI, SwitchDim

HFF = Dimmable with DALI, DSI, SwitchDim

LED\* se [www.zero.se](http://www.zero.se) för teknisk information gällande Led.





LED\* visit [www.zero.se](http://www.zero.se) for technical information regarding LEDs.

**Finish:** White or black painted metal. Diffuser in matt acrylic. The angle of the shade can be adjusted with a wire.


**Installation:** Ceiling hook.

**Connection:** Terminal block 3x4mm<sup>2</sup>. when HFF 5x4mm<sup>2</sup>

**Design:** Tham & Videgård 2009.



7850-1



7850-3