

Enkel och stilren väggarmatur som ger ett bra allmänljus. Finns även med inbyggt nödljus på begäran.

Utförande: Mörkgrå strukturlack. Skärm av matt opalglas.

Montage: På vägg.

Anslutning: Snabbkopplingsplint 5x4mm². Överkopplingsbar. Distans för utanpåliggande ledning finns som tillbehör.

Design: Per Sundstedt.

W	SKÄRM/SHADE	KG	ART
22W/2Gx13	Glas/Glass	2,3	4063-1-21HF
22W/2Gx13	Glas/Glass	2,4	4063-1-21HFF
LED*	Glas/Glass	2,5	4064-1-21
LED*	Glas/Glass	2,5	4064-1-21HFF
LED*	Akryl/Acrylic	1,8	4064-1-27HFF

Med inbyggd närvarosensor/With built-in motion detector

LED*	Glas/Glass	2,5	4064-1-21S
LED*	Glas/Glass	2,5	4064-1-21HFFS

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

LED* se www.zero.se för teknisk information gällande Led.

LED* visit www.zero.se for technical information regarding LEDs.

TILLBEHÖR/ACCESSORY

Distans för utanpåliggande ledning **94063-1-01**

Distance-piece for external mains cable

Närvarosensor till 4064/Motion detector for 4064 **98900-1-01**





Finish: Dark-grey painted steel. Shade in matt opal glass.

Installation: Wall installation.

Connection: Snap-in terminal block 5x4mm². Two cable entries.

Distance-piece for external mains cable available as accessory.

Design: Per Sundstedt.



TAK/CEILING 30-31

PENDLAR/PENDANTS 102

VÄGG/CEILING 130-132