

FUNNEL

Design by Ramón Benedito.

VIBIA
LIGHT IS CREATION

Reference

2010.

Application

Wall Lamps

Installation type

Surface

Description

Aluminium wall light giving an indirect light which is ideal for creating a cosy atmosphere in any room. Non-dazzle. Available in four finishes: chrome and red, black and white lacquer.

Diffuser

Aluminium diffuser

Finish



2010-01.

Chrome

2010-03.

White lacquer


2010-04.

Black lacquer

2010-06.

Red lacquer


Sketch



Electrical characteristics

3 x R7s 80mm 230V 80W Eco

Total 240 W



Physical characteristics

1 Box / 0.27 x 0.60 x 0.60 m. / Vol. 0.0972 m³ /
Gross weight 3.7 kg. / Net weight 3.1 kg.


Installation and assembly

Follow instructions of the installation guide

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Efficiency : 42.47%

Coordinate system : C-G

Total flux : 4350.00 lm

Maximum value : 128.63 cd/klm

Light position : C=90.00 G=75.00

Double symmetrical : 3

Isolux : Isolux (Suelo)

Light position :

X=0.00m Y=0.00m Z=3.00m

Light rotation :

Certificates

