

FUNNEL

Design by Ramón Benedito.

VIBIA
LIGHT IS CREATION

Reference

2011.

Application

Wall Lamps

Installation type

Surface

Description

Aluminium wall light giving an indirect light which is ideal for creating a cosy atmosphere in any room. Non-dazzle. Available in two finishes: white lacquer and gold leaf.

Diffuser


Aluminium diffuser

Finish



2011-03. White lacquer
2011-51. Gold leaf

Sketch




Electrical characteristics

1 x 2GX13 230V 22W (T5C)



Total 22 W



Physical characteristics

1 Box / 0.27 x 0.60 x 0.60 m. / Vol. 0.0972 m³ /
Gross weight 3.9 kg. / Net weight 3.8 kg.


Installation and assembly

Follow instructions of the installation guide

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Efficiency : 66.82%
Coordinate system : C-G
Total flux : 1800.00 lm
Maximum value : 84.88 cd/klm
Light position : C=75.00 G=65.00
Double symmetrical : 3
Isolux : Isolux (Suelo)
Light position :
X=0.00m Y=0.00m Z=3.00m
Light rotation :

Certificates

