

INVISIBLE ROUND MINI

EINBAUSTRÄHLER RECESSED SPOTLIGHTS FARETTI DA INCASSO

12



D

Einbaugehäuse aus Gips für randlosen Einbau in Gipskartondecken
Für Gipskartondecken von 10–25mm Deckenstärke geeignet
Ruhiges Deckenbild durch zurückversetztes Strahlerelement
SASSO Strahlerelement aus Aluminium separat bestellen
Durch Patentkugelschnapper werkzeuglos einsetzbar
Strahlerelement 355° dreh- und 45° schwenkbar
Variante mit energieeffizienten e² LEDs 1,1W mit hoher Farbwiedergabe
Farbfilter, Linsen, Wabenraster (max. 1 Stk.) und RGB-LED Einsatz als Zubehör


E

Gypsum housing for trimless installation in plasterboard ceilings
Suitable for plasterboard ceilings from 10–25mm
Calm ceiling scene by using offset spotlight
Order SASSO spotlight made of aluminium separately
Patented ball catch system installs without tools
Spotlight 355° rotatable and 45° tiltable
Type with energy efficient e² LEDs 1,1W with high CRI
Colour filters, lenses, louvers (max. 1) and RGB-LED inset available as acc.

I


Cassaforma di gesso a scomparsa per soffitti di cartongesso
Per soffitti di 10–25mm di spessore
Impressione tranquilla grazie al faretto arretrato
Faretto di alluminio SASSO da ordinare separatamente
Inseribile facilmente con brevettato moschettone sferico
Faretto girevole 355° e orientabile 45°
Variante con LED e² da 1,1W con resa cromatica alta
Filtri colorati, lenti, reticoli a nido d'ape e inserti RGB come acc.

Type




INVISIBLE ROUND MINI HOUSING 1 lamp
COLOUR
white gypsum **CODE**
060-02617

Order spotlight separately!



INVISIBLE ROUND MINI HOUSING 2 lamps
COLOUR
white gypsum **CODE**
060-02627

Order spotlight separately!




INVISIBLE ROUND MINI HOUSING 3 lamps
COLOUR
white gypsum **CODE**
060-02637

Order spotlight separately!

Spotlight



SASSO 80 K SPOTLIGHT LED 24V DC
e² LED
CAPACITY **H (MM)** **CODE**
3x1,1W 87 052-1310#1#M
052-... 4_ 2700K 89 lm/led
5_ 3000K 89 lm/led
6_ 4000K 102 lm/led
8_ 6000K 118 lm/led



SASSO 80 K SPOTLIGHT QR-CBC51 GU5.3
QR-CBC51 GU5.3
CAPACITY **H (MM)** **CODE**
1x50W 170 060-6129#



SASSO 80 K SPOTLIGHT HIPAR51 GX10
HIPAR51 GX10
CAPACITY **H (MM)** **CODE**
1x20W 170 060-6629#



0_... 6 grey
7 white
8 black

Accessories




Elektronischer LED Konverter | Transformator
Electronic LED converter | transformer
Convertitore LED | trasformatore elettronico
CAPACITY **L/B/H (MM)** **CODE**
4W LED 100-240V 73/40/16 007-1924200
70VA/230-240V/12V 102/51/30 002-70700
105VA/230-240V/12V 102/51/30 002-71000
150VA/230V/12V 206/45/40 002-71500



Vorschaltgeräteblock mit Kabel und Anschlussstecker
Control gear unit with cable and connector plug
Blocco di reattore elettronico con cavo e connettore a spina
CAPACITY **L/B/H (MM)** **CODE**
20W/220-240V electr. 140/67/31 002-85020



RGB LED INSET 3 3x1,1W 24V DC XAL-BUS
LED COLOUR **BEAM** **CODE**
RGB super spot 6° 055-28996V
RGB spot 15° 055-28996S
RGB medium 24° 055-28996M
RGB wide flood 80° 055-28996W
Use only with spotlight for QR-CBC51 GU5.3
Order XAL DMX power master unit separately
See page 101 for more details



See page 101 for more accessories

Colour and protection filters
Lenses and honeycomb louver