

D

Einbaugehäuse aus Gips für randlosen Einbau in Gipskartondecken
Für Gipskartondecken von 10–25mm Deckenstärke geeignet
Ruhiges Deckenbild durch zurückversetztes Strahlerelement
SASSO Strahlerelement aus Aluminium separat bestellen
Durch Patentkugelschnapper werkzeuglos einsetzbar
Strahlerelement 355° dreh- und 45° schwenkbar
Variante mit energieeffizienten e² LEDs 1,1W mit hoher Farbwiedergabe
Farbfilter, Linsen, Wabenraster (max. 1 Stk.) und RGB-LED Einsatz als Zubehör


E

Gypsum housing for trimless installation in plasterboard ceilings
Suitable for plasterboard ceilings from 10–25mm
Calm ceiling scene by using offset spotlight
Order SASSO spotlight made of aluminium separately
Patented ball catch system installs without tools
Spotlight 355° rotatable and 45° tiltable
Type with energy efficient e² LEDs 1,1W with high CRI
Colour filters, lenses, louvers (max. 1) and RGB-LED inset available as acc.

I

Cassaforma di gesso a scomparsa per soffitti di cartongesso
Per soffitti di 10–25mm di spessore
Impressione tranquilla grazie al faretto arretrato
Faretto di alluminio SASSO da ordinare separatamente
Inseribile facilmente con brevettato moschettone sferico
Faretto girevole 355° e orientabile 45°
Variante con LED e² da 1,1W con resa cromatica alta
Filtri colorati, lenti, reticoli a nido d'ape e inserti RGB come acc.

Type




INVISIBLE ROUND HOUSING 1 lamp

COLOUR
white gypsum

CODE
060-02717

Order spotlight separately!




INVISIBLE ROUND HOUSING 2 lamps

COLOUR
white gypsum

CODE
060-02727

Order spotlight separately!



INVISIBLE ROUND HOUSING 3 lamps

COLOUR
white gypsum

CODE
060-02737

Order spotlight separately!

Spotlight



e² LED

SASSO 150 K SPOTLIGHT LED 24V DC

CAPACITY 12x1,1W **H (MM)** 130 **CODE** 052-1610#1#M

052-... 4... 2700K 89 lm/led
5... 3000K 89 lm/led
6... 4000K 102 lm/led
8... 6000K 118 lm/led



QR-LP 111 G53

SASSO 150 K SPOTLIGHT QR-LP 111 G53

CAPACITY 1x75W **H (MM)** 228 **CODE** 060-6529#



TC-DEL G24q-...

SASSO 150 K SPOTLIGHT TC-DEL G24q-...

CAPACITY 1x18W 1x26W **H (MM)** 273 293 **CODE** 060-6410# 060-6510#



0... 6 grey
7 white
8 black

SASSO 150 K SPOTLIGHT HIT-CE G12

CAPACITY 1x35/70W **H (MM)** 238 **CODE** 060-6829#

060-6829# S spot 14°
M medium 24°
F flood 40°
W wide flood 60°

Accessories



Elektronischer LED Konverter | Transformator

Electronic LED converter | transformer
Convertitore LED | trasformatore elettronico

CAPACITY 18W LED 100-240V **L/B/H (MM)** 153/67/31 **CODE** 007-1924500

70VA/230-240V/12V 102/51/30 002-70700
105VA/230-240V/12V 102/51/30 002-71000
150VA/230V/12V 206/45/40 002-71500



Vorschaltgeräteeinheit mit Kabel und Anschlussstecker

Control gear unit with cable and connector plug
Blocco di reattore elettronico con cavo e connettore a spina

CAPACITY 35W/220-240V electr. 186/89/37 **CODE** 002-86035

70W/220-240V electr. 186/89/37 002-86070




RGB LED INSET 12x1,1W 24V DC XAL-BUS

LED COLOUR **BEAM** **CODE**

RGB super spot 6° 055-27096V
RGB spot 15° 055-27096S
RGB medium 24° 055-27096M
RGB wide flood 80° 055-27096W

Use only with spotlight for QR-LP111 G53
Order XAL DMX power master unit separately
See page 101 for more details



Colour and protection filters

Lenses and honeycomb louver

See page 101 for more accessories