



**D**

Einbaugehäuse aus Gips für randlosen Einbau in Gipskartondecken  
Für Gipskartondecken von 10–25mm Deckenstärke geeignet  
Ruhiges Deckenbild durch zurückversetztes Strahlerelement  
SASSO Strahlerelement aus Aluminium separat bestellen  
Durch Patentkugelschnapper werkzeuglos einsetzbar  
Strahlerelement 355° dreh- und 45° schwenkbar  
Variante mit energieeffizienten e<sup>2</sup> LEDs 1,1W mit hoher Farbwiedergabe  
Farbfilter, Linsen, Wabenraster (max. 1 Stk.) und RGB-LED Einsatz als Zubehör


**E**

Gypsum housing for trimless installation in plasterboard ceilings  
Suitable for plasterboard ceilings from 10–25mm  
Calm ceiling scene by using offset spotlight  
Order SASSO spotlight made of aluminium separately  
Patented ball catch system installs without tools  
Spotlight 355° rotatable and 45° tiltable  
Type with energy efficient e<sup>2</sup> LEDs 1,1W with high CRI  
Colour filters, lenses, louvers (max. 1) and RGB-LED inset available as acc.

**I**

Cassaforma di gesso a scomparsa per soffitti di cartongesso  
Per soffitti di 10–25mm di spessore  
Impressione tranquilla grazie al faretto arretrato  
Faretto di alluminio SASSO da ordinare separatamente  
Inseribile facilmente con brevettato moschettone sferico  
Faretto girevole 355° e orientabile 45°  
Variante con LED e<sup>2</sup> da 1,1W con resa cromatica alta  
Filtri colorati, lenti, reticoli a nido d'ape e inserti RGB come acc.

## Type




**INVISIBLE RETRO HOUSING 1 lamp**

**COLOUR**  
white gypsum

**CODE**  
060-01417

Order spotlight separately!




**INVISIBLE RETRO HOUSING 2 lamps**

**COLOUR**  
white gypsum

**CODE**  
060-01427

Order spotlight separately!



**INVISIBLE RETRO HOUSING 3 lamps**

**COLOUR**  
white gypsum

**CODE**  
060-01437

Order spotlight separately!

## Accessories



**Elektronischer LED Konverter | Transformator**  
Electronic LED converter | transformer  
Convertitore LED | trasformatore elettronico

CAPACITY	L/B/H (MM)	CODE
18W LED 100-240V	153/67/31	007-1924500
70VA/230-240V/12V	102/51/30	002-70700
105VA/230-240V/12V	102/51/30	002-71000
150VA/230V/12V	206/45/40	002-71500



**Vorschaltgeräteeinheit mit Kabel und Anschlussstecker**  
Control gear unit with cable and connector plug  
Blocco di reattore elettronico con cavo e connettore a spina


CAPACITY	L/B/H (MM)	CODE
35W/220-240V electr.	186/89/37	002-86035
70W/220-240V electr.	186/89/37	002-86070



**RGB LED INSET 12x1,1W 24V DC XAL-BUS**

LED COLOUR	BEAM	CODE
RGB	super spot 6°	055-27096V
RGB	spot 15°	055-27096S
RGB	medium 24°	055-27096M
RGB	wide flood 80°	055-27096W

Use only with spotlight for QR-LP111 G53  
Order XAL DMX power master unit separately  
See page 101 for more details



**Colour and protection filters**  
Lenses and honeycomb louver

See page 101 for more accessories

## Spotlight



**SASSO 150 K SPOTLIGHT LED 24V DC**

**e<sup>2</sup> LED**

CAPACITY	H (MM)	CODE
12x1,1W	130	052-1610#1#M
052-...4...	2700K	89 lm/led
6...	3000K	89 lm/led
6...	4000K	102 lm/led
8...	6000K	118 lm/led




**SASSO 150 K SPOTLIGHT QR-LP 111 G53**

CAPACITY	H (MM)	CODE
1x75W	228	060-6529#



**SASSO 150 K SPOTLIGHT TC-DEL G24q-...**

CAPACITY	H (MM)	CODE
1x18W	273	060-6410#
1x26W	293	060-6510#



**SASSO 150 K SPOTLIGHT HIT-CE G12**

CAPACITY	H (MM)	CODE
1x35/70W	238	060-6829#

060-6829#S spot 14°  
M medium 24°  
F flood 40°  
W wide flood 60°

6	7	8	0...6 grey
			7 white
			8 black