




**D**  
Einbaugehäuse aus Gips für randlosen Einbau in Gipskartondecken  
Für Gipskartondecken von 10–25mm Deckenstärke geeignet  
Ruhiges Deckenbild durch zurückversetztes Strahlerelement  
SASSO Strahlerelement aus Aluminium separat bestellen  
Durch Patentkugelschnapper werkzeuglos einsetzbar  
Strahlerelement 355° dreh- und 45° schwenkbar  
Variante mit energieeffizienten e<sup>2</sup> LEDs 1,1W mit hoher Farbwiedergabe  
Farbfilter, Linsen, Wabenraster (max. 1 Stk.) und RGB-LED Einsatz als Zubehör

**E**  
Gypsum housing for trimless installation in plasterboard ceilings  
Suitable for plasterboard ceilings from 10–25mm  
Calm ceiling scene by using offset spotlight  
Order SASSO spotlight made of aluminium separately  
Patented ball catch system installs without tools  
Spotlight 355° rotatable and 45° tiltable  
Type with energy efficient e<sup>2</sup> LEDs 1,1W with high CRI  
Colour filters, lenses, louvers (max. 1) and RGB-LED inset available as acc.


**I**  
Cassaforma di gesso a scomparsa per soffitti di cartongesso  
Per soffitti di 10–25mm di spessore  
Impressione tranquilla grazie al faretto arretrato  
Faretto di alluminio SASSO da ordinare separatamente  
Inseribile facilmente con brevettato moschettone sferico  
Faretto girevole 355° e orientabile 45°  
Variante con LED e<sup>2</sup> da 1,1W con resa cromatica alta  
Filtri colorati, lenti, reticoli a nido d'ape e inserti RGB come acc.

## Type




**INVISIBLE SQUARE MINI HOUSING 1 lamp**  
**COLOUR**  
white gypsum **CODE**  
060-02017

Order spotlight separately!



**INVISIBLE SQUARE MINI HOUSING 2 lamps**  
**COLOUR**  
white gypsum **CODE**  
060-02027

Order spotlight separately!



**INVISIBLE SQUARE MINI HOUSING 3 lamps**  
**COLOUR**  
white gypsum **CODE**  
060-02037

Order spotlight separately!

## Spotlight



**SASSO 80 K SPOTLIGHT LED 24V DC**  
**e<sup>2</sup> LED**  
**CAPACITY** **H (MM)** **CODE**  
3x1,1W 87 052-1310#1#M  
052-... 4\_ 2700K 89 lm/led  
5\_ 3000K 89 lm/led  
6\_ 4000K 102 lm/led  
8\_ 6000K 118 lm/led



**SASSO 80 K SPOTLIGHT QR-CBC51 GU5.3**  
**QR-CBC51 GU5.3**  
**CAPACITY** **H (MM)** **CODE**  
1x50W 170 060-6129#



**SASSO 80 K SPOTLIGHT HIPAR51 GX10**  
**HIPAR51 GX10**  
**CAPACITY** **H (MM)** **CODE**  
1x20W 170 060-6629#



0\_... 6 grey  
7 white  
8 black

## Accessories



**Elektronischer LED Konverter | Transformator**  
Electronic LED converter | transformer  
Convertitore LED | trasformatore elettronico

<b>CAPACITY</b>	<b>L/B/H (MM)</b>	<b>CODE</b>
4W LED 100-240V	73/40/16	007-1924200
70VA/230-240V/12V	102/51/30	002-70700
105VA/230-240V/12V	102/51/30	002-71000
150VA/230V/12V	206/45/40	002-71500



**Vorschaltgeräteblock mit Kabel und Anschlussstecker**  
Control gear unit with cable and connector plug  
Blocco di reattore elettronico con cavo e connettore a spina


<b>CAPACITY</b>	<b>L/B/H (MM)</b>	<b>CODE</b>
20W/220-240V electr.	140/67/31	002-85020



**RGB LED INSET 3** 3x1,1W 24V DC XAL-BUS

<b>LED COLOUR</b>	<b>BEAM</b>	<b>CODE</b>
RGB	super spot 6°	055-28996V
RGB	spot 15°	055-28996S
RGB	medium 24°	055-28996M
RGB	wide flood 80°	055-28996W

Use only with spotlight for QR-CBC51 GU5.3  
Order XAL DMX power master unit separately  
See page 101 for more details



Colour and protection filters  
Lenses and honeycomb louver

See page 101 for more accessories