




D
Einbaugehäuse aus Gips für randlosen Einbau in Gipskartondecken
Für Gipskartondecken von 10–25mm Deckenstärke geeignet
Ruhiges Deckenbild durch zurückversetztes Strahlerelement
SASSO Strahlerelement aus Aluminium separat bestellen
Durch Patentkugelschnapper werkzeuglos einsetzbar
Strahlerelement 355° dreh- und 45° schwenkbar
Variante mit energieeffizienten e² LEDs 1,1W mit hoher Farbwiedergabe
Farbfilter, Linsen, Wabenraster (max. 1 Stk.) und RGB-LED Einsatz als Zubehör


E
Gypsum housing for trimless installation in plasterboard ceilings
Suitable for plasterboard ceilings from 10–25mm
Calm ceiling scene by using offset spotlight
Order SASSO spotlight made of aluminium separately
Patented ball catch system installs without tools
Spotlight 355° rotatable and 45° tiltable
Type with energy efficient e² LEDs 1,1W with high CRI
Colour filters, lenses, louvers (max. 1) and RGB-LED inset available as acc.

I
Cassaforma di gesso a scomparsa per soffitti di cartongesso
Per soffitti di 10–25mm di spessore
Impressione tranquilla grazie al faretto arretrato
Faretto di alluminio SASSO da ordinare separatamente
Inseribile facilmente con brevettato moschettone sferico
Faretto girevole 355° e orientabile 45°
Variante con LED e² da 1,1W con resa cromatica alta
Filtri colorati, lenti, reticoli a nido d'ape e inserti RGB come acc.


Type



INVISIBLE SQUARE HOUSING 1 lamp
COLOUR
white gypsum **CODE**
060-02117
Order spotlight separately!



INVISIBLE SQUARE HOUSING 2 lamps
COLOUR
white gypsum **CODE**
060-02127
Order spotlight separately!



INVISIBLE SQUARE HOUSING 3 lamps
COLOUR
white gypsum **CODE**
060-02137
Order spotlight separately!

Spotlight



SASSO 150 K SPOTLIGHT LED 24V DC
e² LED
CAPACITY **H (MM)** **CODE**
12x1,1W 130 052-1610#1#M
052-...4... 2700K 89 lm/led
5... 3000K 89 lm/led
6... 4000K 102 lm/led
8... 6000K 118 lm/led




SASSO 150 K SPOTLIGHT QR-LP 111 G53
CAPACITY **H (MM)** **CODE**
1x75W 228 060-6529#



SASSO 150 K SPOTLIGHT TC-DEL G24q-...
CAPACITY **H (MM)** **CODE**
1x18W 273 060-6410#
1x26W 293 060-6510#



SASSO 150 K SPOTLIGHT HIT-CE G12
CAPACITY **H (MM)** **CODE**
1x35/70W 238 060-6829#
060-6829#S spot 14°
M medium 24°
F flood 40°
W wide flood 60°



Accessories




Elektronischer LED Konverter | Transformator
Electronic LED converter | transformer
Convertitore LED | trasformatore elettronico
CAPACITY **L/B/H (MM)** **CODE**
18W LED 100-240V 153/67/31 007-1924500
70VA/230-240V/12V 102/51/30 002-70700
105VA/230-240V/12V 102/51/30 002-71000
150VA/230V/12V 206/45/40 002-71500



Vorschaltgeräteblock mit Kabel und Anschlussstecker
Control gear unit with cable and connector plug
Blocco di reattore elettronico con cavo e connettore a spina
CAPACITY **L/B/H (MM)** **CODE**
35W/220-240V electr. 186/89/37 002-86035
70W/220-240V electr. 186/89/37 002-86070



RGB LED INSET 12x1,1W 24V DC XAL-BUS
LED COLOUR **BEAM** **CODE**
RGB super spot 6° 055-27096V
RGB spot 15° 055-27096S
RGB medium 24° 055-27096M
RGB wide flood 80° 055-27096W
Use only with spotlight for QR-LP111 G53
Order XAL DMX power master unit separately
See page 101 for more details



See page 101 for more accessories
Colour and protection filters
Lenses and honeycomb louver