




D
 Einbaugehäuse aus Gips für randlosen Einbau in Gipskartondecken
 Für Gipskartondecken von 9-30mm Deckenstärke geeignet
 Ruhiges Deckenbild durch zurückversetztes Strahlerelement
 SASSO Strahlerelement aus Aluminium separat bestellen
 Durch Patentkugelschnapper werkzeuglos einsetzbar
 Strahlerelement 355° dreh- und 45° schwenkbar
 Variante mit energieeffizienten e² LEDs 1,1W mit hoher Farbwiedergabe
 Farbfilter, Linsen, Wabenraster (max. 1 Stk.) und RGB-LED Einsatz als Zubehör


E
 Gypsum housing for trimless installation in plasterboard ceilings
 Suitable for plasterboard ceilings from 9-30mm
 Calm ceiling scene by using offset spotlight
 Order SASSO spotlight made of aluminium separately
 Patented ball catch system installs without tools
 Spotlight 355° rotatable and 45° tiltable
 Type with energy efficient e² LEDs 1,1W with high CRI
 Colour filters, lenses, louvers (max. 1) and RGB-LED inset available as acc.

I
 Cassaforma di gesso a scomparsa per soffitti di cartongesso
 Per soffitti di 9-30mm di spessore
 Impresione tranquilla grazie al faretto arretrato
 Faretto di alluminio SASSO da ordinare separatamente
 Inseribile facilmente con brevettato moschettone sferico
 Faretto girevole 355° e orientabile 45°
 Variante con LED e² da 1,1W con resa cromatica alta
 Filtri colorati, lenti, reticoli a nido d'ape e inserti RGB come acc.

Type



BUBBLE MINI HOUSING
COLOUR
 white gypsum **CODE**
 060-02817
 Order spotlight separately!




BUBBLE MEDIUM HOUSING
COLOUR
 white gypsum **CODE**
 060-02917
 Order spotlight separately!

Spotlight




SASSO 80 K SPOTLIGHT LED 24V DC
e² LED
CAPACITY **H (MM)** **CODE**
 3x1,1W 97 052-1310#1#M
 052-... 4... 2700K 89 lm/led
 5... 3000K 89 lm/led
 6... 4000K 102 lm/led
 8... 6000K 118 lm/led



SASSO 80 K SPOTLIGHT QR-CBC51 GU5.3
CAPACITY **H (MM)** **CODE**
 1x50W 180 060-6129#



SASSO 100 K SPOTLIGHT LED 24V DC
e² LED
CAPACITY **H (MM)** **CODE**
 6x1,1W 115 052-1410#1#M
 052-... 4... 2700K 89 lm/led
 5... 3000K 89 lm/led
 6... 4000K 102 lm/led
 8... 6000K 118 lm/led



SASSO 100 K SPOTLIGHT QT12-LP GY6,35
CAPACITY **H (MM)** **CODE**
 1x50W 135 060-5219#



SASSO 100 K SPOTLIGHT HIT-TC-CE GU6,5
CAPACITY **H (MM)** **CODE**
 1x20W 135 060-5319#

060-... S spot 14°
 M medium 24°
 E flood 40°

0... 6 grey
 7 white
 8 black

Accessories



Elektronischer LED Konverter | Transformator
 Electronic LED converter | transformer
 Convertitore LED | trasformatore elettronico
CAPACITY **L/B/H (MM)** **CODE**
 4W LED 100-240V 73/40/16 007-1924200
 70VA/230-240V/12V 102/51/30 002-70700
 105VA/230-240V/12V 102/51/30 002-71000
 150VA/230V/12V 206/45/40 002-71500




Vorschaltgeräteblock mit Kabel und Anschlussstecker
 Control gear unit with cable and connector plug
 Blocco di reattore elettronico con cavo e connettore a spina
CAPACITY **L/B/H (MM)** **CODE**
 20W/220-240V electr. 140/67/31 002-85020



RGB LED INSET 3 3x1,1W 24V DC XAL-BUS
LED COLOUR **BEAM** **CODE**
 RGB super spot 6° 055-28996V
 RGB spot 15° 055-28996S
 RGB medium 24° 055-28996M
 RGB wide flood 80° 055-28996W

Use only with spotlight for QR-CBC51 GU5,3
 Order XAL DMX power master unit separately
 See page 101 for more details



Colour and protection filters
 Lenses and honeycomb louver

See page 101 for more accessories