

LASTRA 6

Mounting	: Suspension
Type of ceiling pendant	: Suspension cable
Lamps description	: 6 x MAX 35W GU4 HRG
Environment	: Indoor
Finish	: Crystal plate
Technical description	: Suspension fixture providing direct lighting. Lamp body formed by a rectangular, tempered transparent glass sheet, thickness 15 mm. 6 pressed with white finish glass diffusers. Injection-molded transparent polycarbonate diffuser support and black PPS lamp-holder. Aluminum attachment grid. Power is distributed to the light sources through two silkscreening processes: deposition of a highly conductive silver paste, followed by deposition of a protective ceramic paint. 2 electronic transformers fitted on the glass sheet with IGBT type wall dimmer. 4 steel suspension cables and 4 mechanical, die-cast, polished aluminum ceiling fittings, with built-in quick adjustment cord. 30% fiberglass reinforced polyamide wired ceiling fitting; gray painted, injection-molded polycarbonate rose.

ELECTRICAL

Transformer availability	: Inclusi
Transformer mounting	: Integral
Emergency	: Without
Voltage (V)	: 230/240

PHYSICAL

Supply	: Terminal block
Construction material	: Aluminum or Glass or Polycarbonate
Weight (kg)	: 17



Lastra 6
design by Antonio Citterio with Oliver Löw

Suspension lamp providing direct light

Reference Code

● **F3361000** **Crystal plate**

Certifications

