



Downlight för belysning av konferensrum, korridorer, entréhallar mm.

**Utförande:** Vitlackerad metall. Matt optiskt glas. Bländskydd av opal akryl ovan glas är standard till storlek 1000 mm. Finns som tillbehör till storlek 330 och 500.

**Montage:** Infäld i ventilerat alt. oventilerat undertak.

**Anslutning:** Snabbkopplingsplint 5x4mm<sup>2</sup>. Överkopplingsbar.

**Design:** Per Sundstedt.

W	D	KG	ART
2x24W/2G10	330	2,7	7400-1-01HF
2x24W/2G10	330	2,7	7400-1-01HFF
4x24W/2G10	500	3,5	7400-3-01HF
4x24W/2G10	500	3,5	7400-3-01HFF
6x36W/2G11	1000	5,9	7400-5-01HF
6x36W/2G11	1000	5,9	7400-5-01HFF

HFF = Dimmbart driftdon. Fördunklas via DSI alt. SwitchDIM. Dali på begäran.

HFF = Dimmable ballast SwitchDim/DSI, available with Dali on request.

### TILLBEHÖR/ACCESSORIES

#### ART

Opal akryl bländskydd 330/Opal acrylic diffuser. **97401-1-27**

Opal akryl bländskydd 500/Opal acrylic diffuser. **97401-3-27**

Montageplåt mjuka tak 330/Support-frame for soft ceilings **97400-1-01**

Montageplåt mjuka tak 500/Support-frame for soft ceilings **97400-3-01**

Montageplåt mjuka tak 1000/Support-frame for soft ceilings **97400-5-01**

**Finish:** White painted steel. Matt optical glass. Diffuser in opal acrylic above glass is standard for size 1000 mm, available as accessory for sizes 330 och 500.

**Installation:** Recessed.

**Connection:** Snap-in terminal block 5x4mm<sup>2</sup>. Two entry holes.

**Design:** Per Sundstedt.

