

Bowi ger ett effektivt och mjukt ljus genom den vita tygskärmen. Fungerar lika bra på kontoret som i övriga allmänna utrymmen.

Utförande: Vitlackerad metall. Flamskyddat tyg Kvadrat Palet 2. Tvättbar 60°. Vid glödljusutförande är duken perforerad och vid lysrör tät.

Montage: Dikt tak.

Anslutning: Snabbkopplingsplint 5x4mm². Överkopplingsbar.

Design: Per Sundstedt.

W	MM	KG	ART
2x36W/2G11	1000	5,2	3130-1-39HF
2x36W/2G11	1000	5,2	3130-1-39HFF
4x36W/2G11	1000	5,5	3131-1-39HF
4x36W/2G11	1000	5,5	3131-1-39HFF

4xE14	800	5,1	3132-1-39
-------	-----	-----	-----------

HFF = Dimmbart driftdon. Fördunklas via SwitcDIM alt. DSI Dali på begäran.

HFF = Dimmable ballast SwitchDim/DSI, available with Dali on request.

TILLBEHÖR/ACCESSORIES	L/MM	
Undertaksprofil/Support for soft ceiling	600	93130-1-01
Undertaksprofil/Support for soft ceiling	1200	93130-3-01

LJUSKÄLLA E14/LIGHT SOURCE E14	
18W/Halogen Eco	L70026
7W/Lägenenergi/low energy	L70022
1,6W LED	L70027

Finish: White painted steel. Fire protected fabric Kvadrat Palet 2. Washable 60°. Art no. 3132-1-39 has perforated fabric.

Installation: Ceiling-installation.

Connection: Snap-in terminal block 5x4mm². Two cable entries.

Design: Per Sundstedt.

