



Utförande: Oljad alt. svartbetsad ekfanér. Bländskydd av matt akryl, vid metallhalogen klart täckglas Kan även tillverkas i andra träslag och ytbehandlingar på begäran. Finns med ett flertal olika ljuskällor. 26-32W kompaktlysrör, 35W metallhalogen alt. LED Philips Fortimo 2000 lumen med ljusfärg 830 alt. 840.

Montage: Dikt tak.

Anslutning: Snabbkopplingsplint 5x4mm². Överkopplingsbar.

Design: Fredrik Mattson 2010.

W	FÄRG/FINISH	ART
26-32W/Gx24q	Oljad ek/Oiled oak	8000-1-32
26-32W/Gx24q	Svart ek/Black oak	8000-1-36
32W/Gx24q	Oljad ek/Oiled oak	8000-1-32HFF
32W/Gx24q	Svart ek/Black oak	8000-1-36HFF
35W/G12	Oljad ek/Oiled oak	8001-1-32
35W/G12	Svart ek/Black oak	8001-1-36
LED/2000Lm/830	Oljad ek/Oiled oak	8002-1-32
LED/2000Lm/830	Svart ek/Black oak	8002-1-36
LED/2000Lm/840	Oljad ek/Oiled oak	8003-1-32
LED/2000Lm/840	Svart ek/Black oak	8003-1-36

HFF = Dimmbart driftdon. Fördunklas via SwitchDim/DSI. Dali på begäran.



HFF = Dimmable ballast SwitchDim/DSI, available with Dali on request.

Finish: Oiled oak veneer natural or black stained. Matt acrylic diffuser. When metal halide clear glass. Available in other wood finishes and stains on request. Available with several light sources. 26-32W compact fluorescent, 35W metal halide and LED Philips Fortimo 2000 lumen in light-color 830 or 840.

Installation: On ceiling.

Connection: Terminal block 5x4mm². Two entry holes.

Design: Fredrik Mattson 2010.



PENDLAR/PENDANTS 48-49

VÄGG/WALL 98

BORD/TABLE 130