

SASSO 150 K | S

EINBAUSTRÄHLER RECESSED SPOTLIGHTS FARETTI DA INCASSO

42




D
Strahlerelement aus Aluminium, 355° dreh-, 45° schwenkbar
Wechselreflektoren aus Reinaluminium in 4 Ausstrahlwinkeln
Set für randlosen Einbau in Gipskartondecken 8-25mm
Einbau für Zwischendecken von 2-25mm
Durch Patentrekugelschnapper werkzeuglos einsetzbar
Betriebsgeräteanschluss der HIT Varianten mittels Stecker
Variante mit energieeffizienten e² LEDs 1,1W mit hoher Farbwiedergabe
Farbfilter, Linsen, Wabenraster (max. 1 Stk.) und RGB-LED Einsatz als Zubehör

E
Spotlight made of aluminium, 355° rotatable, 45° tiltable
Changeable reflectors made of pure aluminium, 4 beam angles
Mounting set for trimless install. in plasterboard ceilings 8-25mm
Mounting ring for ceilings from 2-25mm
Patented ball catch system installs without tools
Plug connection for control gear of HIT type
Type with energy efficient e² LEDs 1,1W with high CRI
Colour filters, lenses, louvers (max. 1) and RGB-LED inset available as acc.

I
Faretto in alluminio, girevole 355°, orientabile 45°
Riflettori d'alluminio puro cambiabili di 4 angoli
Set da montaggio a livello in soffitti di cartongesso 8-25mm
Anello di montaggio per controsoffitti di 2-25mm
Inseribile facilmente con brevettato moschettone sferico
Varianti HIT: Connettore per collegare il reattore
Variante con LED e² da 1,1W con resa cromatica alta
Filtri colorati, lenti, reticoli a nido d'ape e inserti RGB come acc.


Type



SASSO 150 K SPOTLIGHT LED 24V DC

CAPACITY	CODE
12x1,1W	052-1610#1M

052-... 4_ 2700K 89 lm/led
5_ 3000K 89 lm/led
6_ 4000K 102 lm/led
8_ 6000K 118 lm/led




SASSO 150 K SPOTLIGHT QR-LP 111 G53

CAPACITY	H (MM)	CODE
1x100W	150	060-6529#

SASSO 150 K SPOTLIGHT TC-DEL G24q-...


CAPACITY	H (MM)	CODE
1x18W	195	060-6410#
1x26W	215	060-6510#



SASSO 150 K SPOTLIGHT HIT-CE G12


CAPACITY	CODE
1x35/70W	060-6829#

060-6829#S spot 14°
M medium 24°
F flood 40°
W wide flood 60°



SASSO 150 S SPOTLIGHT QR-LP 111 G53

CAPACITY	CODE
1x75W	060-6519#



SASSO 150 S SPOTLIGHT HIT-CE G12

CAPACITY	CODE
1x35/70W	060-6819#

060-6819#S spot 14°
M medium 24°
F flood 40°
W wide flood 60°

Colours



0_...4 chrome
6 grey
7 white
8 black

Accessories



TRIMLESS
Einbauset für randlosen Einbau in Gipskartondecken
Mounting set for trimless installation in plasterboard ceilings
Attrezzo di montaggio per soffitti di cartongesso a scomparsa

Ø/CEILING THICKNESS (MM)	CODE
150/8-25	052-192261#



WITH TRIM
Einbau für Zwischendecken von 2-20mm
Mounting ring for intermediate ceilings 2-20mm
Anello di montaggio per controsoffitti di 2 a 20mm

Ø/CEILING THICKNESS (MM)	CODE
160/2-25	052-192261#



Betoneinbaugehäuse für Sichtbeton
Mounting housing for exposed concrete
Corpo per montaggio in calcestruzzo a vista

L/B/H (MM)	CODE
295/295/210	060-00150



Betoneinbaugehäuse für gespachtelte Betondecken
Mounting housing for primed concrete ceilings
Corpo per montaggio in calcestruzzo stuccato

TYPE	Ø/H (MM)	CODE
LED/QR-LP 111	310/165	052-1914610
HIT-CE	310/215	052-1916610



Elektronischer LED Konverter | Transformator
Electronic LED converter | transformer
Convertitore LED | trasformatore elettronico

CAPACITY	L/B/H (MM)	CODE
18W LED 100-240V	153/67/31	007-1924500
70VA/230-240V/12V	102/51/30	002-70700
105VA/230-240V/12V	102/51/30	002-71000
150VA/230V/12V	206/45/40	002-71500



Vorschaltgeräteblock mit Kabel und Anschlussstecker
Control gear unit with cable and connector plug
Blocco di reattore elettronico con cavo e connettore a spina

CAPACITY	L/B/H (MM)	CODE
35W/220-240V electr.	186/89/37	002-86035
70W/220-240V electr.	186/89/37	002-86070



See page 101 for more accessories

RGB LED Inset
Colour and protection filters
Lenses and honeycomb louver





▶ PRIVATE RESIDENCE, VIENNA
Architect: Najjar+Najjar Architects, Vienna

