




D
Strahlerelement aus Aluminium, 355° dreh-, 35° schwenkbar
Oberfläche in chrom, weiß oder schwarz hochglänzend
Wechselreflektoren aus Reinaluminium in 4 Ausstrahlwinkeln
Set für randlosen Einbau in Gipskartondecken 10-25mm
Einbauring für Zwischendecken von 2–20mm
Durch Patentkugelschnapper werkzeuglos einsetzbar
Betriebsgeräteanschluss der HIT Varianten mittels Stecker
Variante mit energieeffizienten e² LEDs 1,1W mit hoher Farbwiedergabe


E
Spotlight made of Aluminium, 355° rotatable, 35° tiltable
Surface in chrome, black or white high gloss
Changeable reflectors made of pure aluminium, 4 beam angles
Trimless mounting set for plasterboard ceilings 10-25mm
Mounting ring for ceilings from 2–20mm
Patented ball catch system installs without tools
Plug connection for control gear of HIT type
Type with energy efficient e² LEDs 1,1W with high CRI

I
Faretto di alluminio, girevole 355° e orientabile 35°
Finitura cromo, bianca o nera lucida
Riflettori d'alluminio puro cambiabili di 4 angoli
Set di montaggio per soffitti di cartongesso 10-25mm
Anello di montaggio per controsoffitti di 2–20mm
Inseribile facilmente con brevettato moschettone sferico
Varianti HIT: Connettore per collegare il reattore
Variante con LED e² da 1,1W con resa cromatica alta


Type



KICK ME LED 24V DC
e² LED
CAPACITY 12x1,1W **CODE** 052-1670#1#M
052-... 4... 2700K 89 lm/led
5... 3000K 89 lm/led
6... 4000K 102 lm/led
8... 6000K 118 lm/led



KICK ME QR-LP 111 G53
QR-LP 111 G53
CAPACITY 1x75W **CODE** 060-9529#



KICK ME HIT-CE G12
HIT-CE G12
CAPACITY 1x35/70W **CODE** 060-9829#
S spot 14°
M medium 24°
F flood 40°
W wide flood 60°

Colours



0... 4 chrome
7 white high gloss
8 black high gloss

Accessories



TRIMLESS
Einbauset für randlosen Einbau in Gipskartondecken
Mounting set for trimless installation in plasterboard ceilings
Attrezzo di montaggio per soffitti di cartongesso a scomparsa
Ø/CEILING THICKNESS (MM) 150/10-25 **CODE** 052-1921610



WITH TRIM
Einbauring für Zwischendecken von 2-20mm
Mounting ring for intermediate ceilings 2-20mm
Anello di montaggio per controsoffitti di 2 a 20mm
Ø/CEILING THICKNESS (MM) 160/2-20 **CODE** 052-192261#



Betoneinbaugehäuse für Sichtbeton
Mounting housing for exposed concrete
Corpo per montaggio in calcestruzzo stuccato
L/B/H (MM) 295/295/210 **CODE** 060-00150



Betoneinbaugehäuse für gespachtelte Betondecken
Mounting housing for primed concrete ceilings
Corpo per montaggio in calcestruzzo stuccato
TYPE **L/B/H (MM)** **CODE**
mounting housing 225/225/130 052-1914310
mount. housing with channel 460/225/130 052-1915310



Elektronischer LED Konverter | Transformator
Electronic LED converter | transformer
Convertitore LED | trasformatore elettronico
CAPACITY **L/B/H (MM)** **CODE**
18W LED 100-240V 153/67/31 007-1924500
70VA/230-240V/12V 102/51/30 002-70700
105VA/230-240V/12V 102/51/30 002-71000
150VA/230V/12V 206/45/40 002-71500



Vorschaltgeräteblock mit Kabel und Anschlussstecker
Control gear unit with cable and connector plug
Blocco di reattore elettronico con cavo e connettore a spina
CAPACITY **L/B/H (MM)** **CODE**
35W/220-240V electr. 186/89/37 002-86035
70W/220-240V electr. 186/89/37 002-86070



See page 101 for more accessories

Colour and protection filters