

MITO FRAME 140

EINBAUSTRÄHLER RECESSED SPOTLIGHTS FARETTI DA INCASSO

86



D

Leuchtgehäuse aus Stahlblech, Strahler aus Aluminium
 Oberfläche in weiß oder schwarz, seidenmatt
 Rahmen aus Stahlblech in chrom, grau, schwarz oder weiß
 Strahlerelement kardanisch gelagert, schwenkbar bis 35°
 Wechselreflektoren aus Reinaluminium in 3 Ausstrahlwinkeln
 Betoneinbaugehäuse für Einbau in Sichtbeton
 Betriebsgeräteanschluss der HIT Varianten mittels Stecker
 Farbfilter, Linsen, Wabenraster (max. 1 Stk.) als Zubehör



E

Luminaire housing made of sheet steel, spotlight made of aluminium
 Surface white or black, semi-gloss
 Frame made of sheet steel in chrome, grey, black or white
 Spotlight gimbal mounted, tiltable up to 35°
 Changeable reflectors made of pure aluminium, 3 beam angles
 Mounting housing for concrete installation available
 Plug connection for control gear of HIT type
 Colour filters, lenses and louvers (max. 1) available as accessories

I

Corpo di lamiera d'acciaio, faretto di alluminio
 Finitura bianca o nera, satinata
 Cornice di lamiera d'acciaio in cromo, grigia, nera o bianca
 Faretto cardanici, orientabili fino a 35°
 Riflettori d'alluminio puro cambiabili di 3 angoli
 Cassaforma per il montaggio in calcestruzzo
 Varianti HIT: Connettore per collegare il reattore
 Filtri colorati, lenti, reticoli a nido d'ape (solo 1 pz.) come acc.



Type



MITO FRAME 140 QT12-LP GY6,35
CAPACITY 1x50W **CODE** 052-245201#_



MITO FRAME 140 HIT-TC-CE GU6,5
CAPACITY 1x20W **CODE** 052-245501#_



MITO FRAME 140 QT12-LP GY6,35
CAPACITY 2x50W **CODE** 052-246201#_



MITO FRAME 140 HIT-TC-CE GU6,5
CAPACITY 2x20W **CODE** 052-246501#_

052-..... **S** spot 14°
M medium 24°
F flood 40°

Colours



052-..... **4** chrome/black
6 grey/black
7 white
8 black



8

Accessories



Elektronischer Transformator
 Electronic transformer
 Trasformatore elettronico

CAPACITY	L/B/H (MM)	CODE
70VA/230-240V/12V	102/51/30	002-70700
105VA/230-240V/12V	102/51/30	002-71000
150VA/230V/12V	206/45/40	002-71500



Vorschaltgeräteblock mit Kabel und Anschlussstecker
 Control gear unit with cable and connector plug
 Blocco di reattore elettronico con cavo e connettore a spina

CAPACITY	L/B/H (MM)	CODE
20W/220-240V electr.	140/67/31	002-85020




Betoneinbaugehäuse für Sichtbeton
 Mounting housing for exposed concrete
 Corpo per montaggio in calcestruzzo a vista

TYPE	L/B/H (MM)	CODE
1 lamp	446/130/163	052-2911410
2 lamps	446/232/163	052-2912410



Betoneinbaugehäuse für gespachtelte Betondecken
 Mounting housing for primed concrete ceilings
 Corpo per montaggio in calcestruzzo stuccato

TYPE	L/B/H (MM)	CODE
1 lamp	446/130/163	052-2911420
2 lamps	446/232/163	052-2912420



See page 101 for more accessories

Colour and protection filters
 Lenses and honeycomb louver