





Type



MINO 20 SUSPENDED LED 220-240V

| CAPACITY | X (MM) | CODE |
|----------|--------|--------------|
| 10x1,1W | 120 | 056-1274#1#F |
| 20x1,1W | 60 | 056-1264#1#F |

| 056-... | ... | ... | ... |
|---------|-------|-----------|-----|
| 4 | 2700K | 89lm/led | |
| 5 | 3000K | 89lm/led | |
| 6 | 4000K | 102lm/led | |



MINO LINE 20 SUSPENDED LED 220-240V

| CAPACITY | CODE |
|----------|--------------|
| 10W | 056-1254#1#O |
| 15W | 056-1244#1#O |

| 056-... | ... | ... |
|---------|-------|----------|
| 5 | 3000K | 70lm/led |
| 6 | 4000K | 88lm/led |

D

Kantiger Leuchtenkörper aus rechteckigem, stranggepressten Aluminiumprofil
Oberfläche Aluminium natur oder schwarz eloxiert, chrom galvanisiert oder weiß mit Strukturlack pulverbeschichtet
Endstück aus massivem Aluminium in 4 Farbvarianten
Energieeffiziente e² LEDs 1,1W mit tiefstrahlendem Aluminiumreflektor
Lieferbar in Lichtfarben 2700K, 3000K und 4000K
Line LEDs mit homogen ausgeleuchteter satiniertes PMMA-Abdeckung
Lieferbar in Lichtfarben 3000K und 4000K
Höhenverstellbare Seilabhangung 2000mm mit integrierter Einspeiseleitung




E

Edged housing made of rectangular, extruded aluminium
Surface in natural or black anodised aluminium, chrome plated or white or black powder coating
End cap made of solid aluminium in 4 colour options
Energy efficient e² LEDs 1,1W with aluminium reflector
Available in the light colours 2700K, 3000K and 4000K
Line LEDs with satin PMMA cover for uniform illumination
Available in the light colours 3000K and 4000K
Adjustable cable suspension 2000mm with integrated feed

I

Corpo in alluminio spigoloso, in profilo di alluminio rettangolare
Superficie in alluminio anod.nat. o nero, galvanizzata cromo o verniciata in bianco strutturato
Testata finale in alluminio massiccio in 4 varianti di colore
e² LED energeticamente efficiente da 1,1 W con riflettore in alluminio potente
Disponibile nei colori di luce 2700K, 3000K e 4000K
LED Line con coperchio satinato in PMMA, omogeneamente illuminato
Disponibile nei colori di luce 3000K e 4000K
Sospensione variabile in altezza, 2000mm, incluso cavo d'alimentazione

Colours



| 056-... | ... |
|---------|--------------|
| 4 | chrome |
| 5 | white/chrome |
| 6 | aluminium |
| 7 | white |
| 8 | black |
| 9 | black/chrome |



4

5

6

7

8

9