



E







Tracklight made of powder coated aluminium
 Surface white, grey or black powder coating
 Spotlight 350° rotatable and 180° tiltable
 Changeable reflectors made of pure aluminium with bayonet, 3 beam angles
 Versions with highly efficient LEDs available with high CRI
 3 phase adaptor optionally with DALI-bus connector
 Toolless mounting of filters, lenses, louvers and anti glare effect adapter











ESP


Reflector de rail electrificado, de aluminio revestido en polvo
 Superficie con barniz estructurado blanco, gris o negro
 Reflector girable 350° y orientable 180°
 Reflectores intercambiables de alum. puro con bayoneta en 3 ángulos de emisión
 Versiones con LED de alta eficiencia disponibles con alta reproducción cromática
 Adaptador trifásico opcional con conexión para DALI-Bus
 Integración sin herramientas de filtros, lentes, louver y tubo amortig. de luz

RU

Spot для шины из алюминия с порошковой окраской
 Поверхность покрыта белой, серой или черной порошковой краской
 Светильник с возможностью поворота на 350° и наклона на 180°
 Сменные отражатели из алюминия, разъем байонет, 3 варианта угла светораспределения, доступны версии с энергоэффективными LED с высоким индексом цветопередачи, 3-х фазный адаптер, опционально с DALI разъемом
 Аксессуары: цветные фильтры, линзы, антистатические решетки

TYPE	
	 <p>TIMO 80 LED</p> <p>TYPE</p> <p>7W LED 460 lm* 9W LED 640 lm* 15W LED 1000 lm* 19W LED 1180 lm*</p> <p>CODE</p> <p>053-0221###_ 053-0222###_ 053-0223###_ 053-0224###_</p> <p>e² LED</p> <p>220-240V</p>
LED COLOUR TEMPERATURE	
	<p>053-...4... 2700K 5... 3000K 6... 4000K</p> <p>* Luminous Flux (3000K flood)</p>
CONTROL	
	<p>053-...1... non dimmable 3... DIM DALI</p>
COLOUR	
	<p>053-...6... grey 7... white 8... black</p>
LED LENSES	
	<p>053-...S... spot 17° M... medium 24° F... flood 38°</p>

ACCESSORY		
COLOUR AND PROTECTION FILTERS		
	<p>TYPE</p> <p>■ dichroic colour filter ■ dichroic colour filter ■ dichroic colour filter ■ dichroic colour filter UV protection filter IR protection filter</p>	<p>Ø/H (MM)</p> <p>70/3 70/3 70/3 70/3 70/3 70/3</p> <p>CODE</p> <p>006-92201 006-92202 006-92203 006-92204 006-92205 006-92206</p>
LENSES AND HONEYCOMB LOUVER		
	<p>TYPE</p> <p>Sculpture lens Flood lens clear Honeycomb louver</p>	<p>Ø/H (MM)</p> <p>70/3 70/3 65/4</p> <p>CODE</p> <p>006-92227 006-92228 006-93113</p>
ANTI-GLARE ADAPTOR		
	<p>TYPE</p> <p>white 65° black 65°</p> <p>white black</p>	<p>Ø/H (MM)</p> <p>70/44 70/44</p> <p>70/44 70/44</p> <p>CODE</p> <p>005-07077 005-07078</p> <p>005-07087 005-07088</p>
XAL DALI TOUCH PANEL 5,7" 24-48V		
	<p>L/B/H (MM)</p> <p>200/150/20</p>	<p>CODE</p> <p>002-59900</p> <p>See page 731 for more details</p>
SURFACE HOUSING POINT OUTLET		
	<p></p> <p>132 Ø 100</p>	<p>COLOUR</p> <p>grey black white</p> <p>CODE</p> <p>282-GA70-1 282-GA70-2 282-GA70-3</p> <p>i not DALI, see page 592 for DALI point outlet</p>
RECESSED HOUSING POINT OUTLET		
	<p></p> <p>105-114 60 Ø 130</p>	<p>COLOUR</p> <p>grey black white</p> <p>CODE</p> <p>282-XTSA76 282-XTSA77 282-XTSA78</p> <p>i not DALI, see page 592 for DALI point outlet</p>
LED CHANGING KIT 220-240V		
	<p></p> <p>16 Ø 50</p>	<p>TYPE</p> <p>7W LED 500 lm* 9W LED 700 lm* 15W LED 1100 lm* 19W LED 1300 lm*</p> <p>Ø/H (MM)</p> <p>50/6 50/6 50/6 50/6</p> <p>CODE</p> <p>007-7011#18 007-7021#18 007-7031#18 007-7041#18</p>

LED COLOUR TEMPERATURE	
	<p>007-...4... 2700K 5... 3000K 6... 4000K</p> <p>* Luminous Flux (3000K)</p>