

Utförande: Lackerad aluminium och metall. Bländskydd av matt akryl. Med reflektor och kompaktlysrör 26, 32 alt 42W. Finns även med Fortimo LED 2000 lumen med ljusfärg 830 alt. 840.

Montage: Delinfälld i tak. Montageplåt för mjuka undertak finns som tillbehör.

Anslutning: Snabbkopplingsplint 5x4mm². Överkopplingsbar.

Design: Fredrik Mattson 2010.

W	D	FÄRG/FINISH	ART
26-42W/Gx24q	330	Vit/White	7970-1-01
42W/Gx24q	330	Vit/White	7970-1-01HFF
26-42W/Gx24q	330	Multi/Multi	7970-1-90
42W/Gx24q	330	Multi/Multi	7970-1-90HFF
LED/2000lm/830	330	Vit/White	7972-1-01
LED/2000lm/840	330	Vit/White	7973-1-01
LED/2000lm/830	330	Multi/Multi	7972-1-90
LED/2000lm/840	330	Multi/Multi	7973-1-90
26-42W/Gx24q	475	Vit/White	7970-3-01
42W/Gx24q	475	Vit/White	7970-3-01HFF
26-42W/Gx24q	475	Multi/Multi	7970-3-90
42W/Gx24q	475	Multi/Multi	7970-3-90HFF
LED/2000lm/830	475	Vit/White	7972-3-01
LED/2000lm/840	475	Vit/White	7973-3-01
LED/2000lm/830	475	Multi/Multi	7972-3-90
LED/2000lm/840	475	Multi/Multi	7973-3-90

HFF = Dimmbart driftdon. Fördunklas med SwitchDim alt. DSI. Dali på begäran.

HFF = Dimmable ballast. Dimmable with SwitchDim or DSI. Dali on request.

TILLBEHÖR/ACCESSORIES

Art

Montagebrygga för mjuka tak 330/ 97400-1-01

Support-frame for soft ceilings

Montagebrygga för mjuka tak 500/ 97400-3-01





Support-frame for soft ceilings

Finish: Painted aluminum and metal. Diffuser in matt acrylic. With reflector. Compact fluorescent 26, 32 or 42W. Available with Philips Fortimo LED 2000 lumen with light color 830 or 840.

Installation: Partly recessed. Support-frame for plaster ceilings available as accessory.

Connection: Terminal block 5x4mm². Two entry holes.

Design: Fredrik Mattson 2010.



PENDLAR/PENDANTS 64-65



VÄGG/WALL 102



BORD/TABLE 98136



UTOMHUS/OUTDOOR 160-161

Utförande: Lackerad aluminium och metall. Bländskydd av matt akryl.

T5 cirkellysrör.

Montage: Delinfälld i tak. Montageplåt för mjuka undertak finns som tillbehör.

Anslutning: Snabbkopplingsplint 5x4mm². Överkopplingsbar.

Design: Fredrik Mattson 2010.

W	D	FÄRG/FINISH	ART
22W/2Gx13	330	Vit/White	7971-1-01
22W/2Gx13	330	Vit/White	7971-1-01HFF
22W/2Gx13	330	Multi/Multi	7971-1-90
22W/2Gx13	330	Multi/Multi	7971-1-90HFF
40W/2Gx13	475	Vit/White	7971-3-01
40W/2Gx13	475	Vit/White	7971-3-01HFF
40W/2Gx13	475	Multi/Multi	7971-3-90
40W/2Gx13	475	Multi/Multi	7971-3-90HFF
55W/2Gx13	475	Vit/White	7971-4-01
55W/2Gx13	475	Vit/White	7971-4-01HFF
55W/2Gx13	475	Multi/Multi	7971-4-90
55W/2Gx13	475	Multi/Multi	7971-4-90HFF

HFF = Dimmbart driftdon. Fördunklas med SwitchDim alt. DSI. Dali på begäran.

HFF = Dimmable ballast. Dimmable with SwitchDim or DSI. Dali on request.






TILLBEHÖR/ACCESSORIES	Art
Montagebrygga för mjuka tak 330/	97400-1-01
Support-frame for soft ceilings	
Montagebrygga för mjuka tak 500/	97400-3-01
Support-frame for soft ceilings	

Finish: Painted aluminum and metal. Diffuser in matt acrylic. T5 circular tube.

Installation: Partly recessed. Support-frame for plaster ceilings available as accessory.

Connection: Terminal block 5x4mm². Two entry holes.

Design: Fredrik Mattson.



PENDLAR/PENDANTS 64-64



VÄGG/WALL 102



BORD/TABLE 136



UTOMHUS/OUTDOOR 160-161

